



) EC-65-LSXT

Digital DLP®-Rearprojection Cube

The new eyevis **EC-65-LSXT** is a modular rear-projection cube with a screen diagonal of 65" and **SXGA resolution (1,280 x 1,024 pixels)**. The EC-65-LSXT uses innovative LED technology for illumination. EC-65-LSXT is a revolutionary development by eyevis and is completely produced in Germany. It is especially designed for applications which require a reliable 24/7 operation. The display technology is based on the DLP® technology (Digital Light Processing) by TEXAS INSTRUMENTS. This superior technology produces high-definition images of the highest quality. Whether you want to display video data or more complex graphics – you will always get a pin sharp image.

Therefore the new eyevis EC-series allows realising completely flexible display walls, providing the highest colour fidelity, a maximum of brilliance and outstanding reliability. Optionally, there is an additional scaler board available with additional input possibilities and further enhancing features.

eyevis attached much importance on the possibility to use their cubes even in critical ambient light conditions or other challenging safety-related problems. The LSXT version uses a 1-chip-DLP® projector with a display resolution of 1,280 x 1,024 pixels. The MTBF of the LED lights lamps is indicated by the manufacturer with >60,000 hours. Thanks to the use of LED light technology, wear parts, such as colour wheels and traditional lamps are no longer necessary. The use of the DLP® technology guarantees that there is no damage to the display, such as "ghost"-images or burn-in effects, even with continuous static images or fixed patterns.



In numerous tests and comparisons the DLP® technology turned out to be the most reliable for continuous operation. The lifetime of the DMD™ chips is about 150,000 hours (MTBF: 650,000 hours). Of course, all the other parts of the device share the same high standards. This results in low service and maintenance costs for our customers.

The EC-65-LSXT has a screen size of 1280 mm width and 1024 mm height and is available with a standard "seamless" frame (0,3 mm). Furthermore, many optimising options, guarantee stable image quality of all cubes for a long period of time through automatic adjustment of values for brightness, contrast and colour.

) ADVANTAGES OF EYEVIS EC CUBES

Outstanding picture quality

- High contrast and best brightness
- Colour uniformity and wide viewing angle
- Latest DLP® technology
- Best visibility in any lighting condition

Integrated optimising options

- Perfect system adjustment with eyeCube software
- Fast and easy parameter setting
- Many status information available
- Optional Multi-Cube Colour-Brightness Adjustment

Availability and reliability

- Extremely long lifetime of the LED lights
- Qualitative high value components
- Especially designed for continuous operation
- Highly efficient maintenance-free heatpipe cooling

Durability

- Durable and constant picture quality on all Cubes
- Modular, highly available display concept for 24/7 operation
- Low service and maintenance costs
- No wear parts as with traditional lamp systems

Ergonomics

- Very low noise level
- No rainbow effects and other DLP-typical artefacts
- Flexible image quality, adjustable parameters
- Completely dust-proof housing

Precision screen concept

- Perfect viewing angle
- Minimum gaps between cubes thanks to clipping method
- Very easy and fast installation

) EC-65-LSXT



Digital DLP®-Rearprojection Cube



) ADVANTAGES COMPARED TO STANDARD LAMP/COLOUR WHEEL SYSTEMS

- Shorter turning-on and start-up sequence compared to conventional lamp systems.
- Real flicker-free representation without rainbow effects and therefore a more ergonomic and fatigue-free observation.
- Higher lifetime with low tear and wear effects, no common wear parts like lamps and colour wheels as with traditional systems.
- Much lower colour and brightness drifts over the life-time of the system, compared with traditional lamp systems.
- High light output and higher lifetime through special colour-interleave method.
- Improved representation of moving images.
- Higher attention to detail, through a better colour gamut and colour space depth.

) TECHNICAL SPECIFICATIONS

Type:	EC-65-LSXT, eyevisCube 65" with LED illumination and native SXGA resolution
Description:	Digital 65" DLP®-rear- projection unit, stackable and addible, for data and video representation
Resolution:	1,280 x 1,024 Pixel (SXGA) / Chip: DMD-Chip SXGA+ / LVDS 0.95"
Processing:	Texas Instruments DDP 3020 (MTBF DMD-Chip: approx. 650,000 hrs according to TI)
Brightness:	typ. 185 cd/m ² (max. 235 cd/m ²)
Contrast Ratio:	1,500:1 (max. 5,000:1 dynamic contrast)
Brightness Uniformity:	≥95%
Image Size (WxH):	1280 x 1024 mm (ca. 65" screen diagonal)
Dimensions (WxHxD):	1280 x 1335 x 850 mm (stair-shaped)
Weight:	approx. 90 kg
Input:	1x DVI-D, optional with Scaler Board: 2x RGB, 2x DVI, 2x Composite Video, 1x Y/C, 1xYUV, 1x S-Video
Projection Screen:	Seamless CrossPrism Screen, viewing angle horizontal & vertical 180°
Frame:	0.3 mm
Power Consumption:	250 Watt at 110/240 VAC
Lamp Life-Time:	60,000 hrs (in recommended operating conditions)
Software:	eyevisCubeManager

Environmental:

Operating Conditions:	recommended 15 - 25 °C; 5 - 35 °C; for Seamless Screen 18 - 25 °C; Storing: 0 - 50 °C
Humidity:	0% - 80 % not condensating
Altitude:	0 - 3000 m
Noise Level:	≤36dB

Options:

	• Scaler Board (internal split controller up to 10x10 Matrix, with 2x DVI, 2x RGB, 2x Video)
	• Multi-Cube Color-Brightness Adjustment
	• Network Board
	• Service and Maintenance Contracts