



) EYE-LCD6500

eyevis LCD Series

) FEATURES

-) Professional 65" (165cm) LCD-Monitor
-) 16:9 Aspect Ratio
-) Low Power Consumption
-) Available for landscape or portrait installation
-) Auto Source Detect
-) Picture-in-Picture, Picture-and-Picture, Zoom-Function
-) Diverse Input Possibilities for best Operating Flexibility
-) Diverse installation possibilities (stands, wall mount, racks, etc.)

) TECHNICAL SPECIFICATION

LCD Panel

Brightness	450 cd/m ²
Contrast Ratio	2000:1
Viewing Angle	176° / 176° (H/V)
Response Time	6.5 ms (GTG)
Colours	16.7 M colours
Max. Picture Resolution	1,920 x 1,080 (full HD) (16:9)
Frame Rate	60 Hz

Display Features

Horizontal Frequency	30 ~ 90 KHz
Vertical Frequency	56 ~ 75 KHz
Input Resolution	1920 x 1080 @ 60 Hz (Analog) / 1920 x 1080 @ 60 Hz (Digital)
OSD Control	RS232C, IR Remote Control, Push Buttons
OSD Language	English, Dutch, French, German, Italian, Norwegian, Portuguese, Russian, Spanish, simplified Chinese, Korean and Swedish

Physical Features

Connectors	2 x HDMI / 2 x Component / 2 x AV / S-Video / VGA / S-PDIF / RS232
Dimensions w/o Stand	1564.3 x 916.0 x 166.8 mm (WxHxD)
Dimensions with Stand	1564.3 x 974.4 x 400 mm (WxHxD)
Weight	ca. 88 kg

Special Features

Multimedia	PIP, PBP (side by side), Over Scan
Auto-Source Detection	Yes
Communication Port (Transport Protocol)	D-Sub 9pin In, RJ45 In/Out, (RS232C In, RS-485 In/Out)
Video Support	HDMI 1.2 with HDCP
Front LED	on / off

Power Consumption

Power Supply	AC 100V ~ 240V (50/60 Hz)
Normal Operation	625 W
Power Saving	8 W

Environmental

Temperature	Operation: 5 - 40 °C / Storage: -20 - 60 °C
Humidity	Operation: 85% RH / Storage: 85% RH

Options

Protective Surface	Tempered Glass
IPC	DSA-3300
Wall Mounting	400 mm x 800 mm



eyevis UK Ltd

PO Box 482 • Burnley
Lancashire • BB11 9BX • United Kingdom
Tel: +44(0)1282 606525 • Fax: +44(0)1282 697703
www.eyevis.co.uk • enquiry@eyevis.co.uk
As at: August 2009 • Subject to change!
Copyright © 2009 eyevis GmbH. All Rights Reserved.