

) EYE-LCD7000

eyevis LCD Series

) DISPLAY CHARACTERISTICS

- ▶ Professional 70 inch LCD-Monitor with S-PVA TFT-Display Panel
- ▶ Full HD resolution
- ▶ 16:9 Aspect Ratio
- ▶ Various Input Possibilities

) TECHNICAL SPECIFICATIONS

LCD Panel

Technology	S-PVA LCD
Max. Image Resolution	1.920 x 1.080 (full HD)

Display Features

Colours	16.7 Millionen (8bits-true)
Aspect Ratio	16:9
Viewing Angle	178° / 178°
Response Time	8 ms (Grey-to-Grey)
Contrast Ratio	1500:1
Brightness	600 cd/m ² (Typical)

Connectors & Control

Inputs	D-SUB 15P (Analog RGB 0.7Vp), DVI, RS232, S-video, CVBS
Supported Resolutions	Input Pixelclock : Max 205MHz (ADC), 640x480 (60Hz) ~ 1920x1080 (60Hz)
Control	IR Remote Control

Power Supply

Input Voltage	100-120 V / 220-240 V; Integrated Mains Adapter
Power Consumption	700 Watt (max. 1000 Watt)

Environmental


Temperature	0-40°C (<50%RH)
Humidity	20-80%RH (T<40°C)

More

Screen Diagonal	70" (177.8 cm)
Screen Area	1630 x 952 mm
Dimensions (WxHxD)	1677.6 x 999.6 x 148 mm
Weight	95 kg

Dimensions:

- A: 1677.6 mm
- B: 999.6 mm
- C: 148 mm



eyevis UK Ltd

PO Box 482 • Burnley
 Lancashire • BB11 9BX • United Kingdom
 Tel: +44(0)1282 606525 • Fax: +44(0)1282 697703
 www.eyevis.co.uk • enquiry@eyevis.co.uk
 As at: August 2009 • Subject to change!
 Copyright © 2009 eyevis GmbH. All Rights Reserved.